



800.882.5292

EVERYDAY STRENGTH.

Designed and tested to do the heavy lifting day after day, week after week.



Lifters



Perkins makes the lifter you need. Call us if you see the lifer you need, or call us if you don't. We design and manufacture the most powerful and most reliable lifters.


Perkins is the industry leader and manufactures more than 30 products and accessories for the waste industry (residential and industrial and commercial users). Perkins customers have chosen Perkins products for their durability, reliability and dependability. Perkins products are distributed primarily through wholesale distributors and longstanding OEM agreements. Please feel free to [contact your sales representative](#) if you have any questions.






Perkins manufactures the solutions you need. If you don't see what you are looking for, just call us. Here is a sample of our capabilities:

Search

Go

Reset

Product	Name	Parameters	Description
	D6025B	<p>Load Type: Rearload without kick-bar</p> <p>Description: US 2-Bar; Type B (ANSI Z245.60-2008)</p> <p>Operation: Cylinder</p> <p>width: 17 inches</p> <p>height: 17 7/8 inches</p> <p>Mounting: 36 - 39</p>	<h2>Cylinder Lifter</h2> <p>The D6025b offers heavy duty construction combined with a simple cylinder design, ensuring reliable lifts throughout the life of the lifter. The sliding lower latch feature allows this unit to have a high ground clearance. Additional benefits include powder coated finish, plastic upper saddle, and a one year warranty.</p>

	<p>D6064</p>	<p>Height: inches</p> <p>Load Type: Frontload</p> <p>Description: US 2-Bar; Type B (ANSI Z245.60-2008)</p> <p>Operation: Pneumatic</p>	<h2 style="text-align: center;">Pneumatic Front-loading Lifter</h2> <p style="text-align: center;">The D6064 allows residential pick-up on a commercial front-loader. Don't send two trucks to a distant location when one truck can do both jobs! Attaches easily to any front-loading truck.</p> <p style="text-align: right;">More</p>
	<p>D6064B</p>	<p>Load Type: Frontload</p> <p>Description: US 2-Bar; Type B (ANSI Z245.60-2008)</p> <p>Operation: Pneumatic</p>	<h2 style="text-align: center;">Pneumatic Front-loading Lifter</h2> <p style="text-align: center;">The D6064b model offers a permanently fixed face plate for front-load collection units. This easily installed product, provides you with an simple and cost effective solution.</p> <p style="text-align: right;">More</p>
	<p>D6070-27k</p>	<p>Load Type: Sideload Frontload Rearload without kick-bar</p> <p>Description: US 2-Bar; Type B (ANSI Z245.60-2008)</p> <p>Operation: Helical Rotary Actuator with 27,000 inch-lbs of torque at 3000 psi</p> <p>width: 21 3/8 inches</p> <p>height: 23 inches</p> <p>Mounting Height: 39 1/2 inches</p>	<h2 style="text-align: center;">Rotary Compact Short Arm Lifters</h2> <p style="text-align: center;">Available in four standard mounting heights, this model is ideal for side-loaders. Like the original compact lifters, it dumps high and deep using a design that minimizes space. New sliding hook feature eliminates the need for a spring plunger and lower stop, allowing the unit to enjoy a wider mounting height range.</p> <p style="text-align: right;">More</p>
	<p>D6071-27k</p>	<p>Load Type: Sideload Frontload Dockside</p> <p>Description: US 2-Bar; Type B (ANSI Z245.60-2008)</p> <p>Operation: Helical Rotary Actuator with 27,000 inch-lbs of torque at 3000 psi</p> <p>width: 21 3/8 inches</p> <p>height: 27 inches</p> <p>Mounting Height: 43 1/2 inches</p>	<h2 style="text-align: center;">Rotary Compact Long Arm Lifters</h2> <p style="text-align: center;">The Compact lifter offers a rugged design with a thin profile that works well in a wide range of applications. Whether mounted to a front load carry-can, rear-loader, or side-loader, these models are workhorses that lift carts high and deep for maximum dumping performance.</p> <p style="text-align: right;">More</p>
	<p>D6071X-27k</p>	<p>Load Type: Side-load Dockside Front-load</p> <p>Description: US 2-Bar; Type B (ANSI Z245.60-2008)</p> <p>Operation: Helical Rotary Actuator with 27,000 inch-lbs of torque at</p>	<h2 style="text-align: center;">Rotary Compact Extra Long Arm Lifters</h2> <p style="text-align: center;">Available in four standard mounting heights, this model is ideal for side-loaders. Dumps high and deep using a design that minimizes space. Now with a more powerful 27k helical rotary actuator. Additionally, Perkins offers several powder coat color options that will go along with your truck or companies color designs.</p>

[More](#)

3000 psi
width: 21 3/8 inches
height: 30 3/4 inches
Mounting 47 1/2 in.
Height:



D6073-
27k

Load Type: Sideload
Description: US 2-Bar; Type B (ANSI Z245.60-2008)
Operation: Helical Rotary Actuator with 27,000 inch-lbs of torque at 3000 psi
width: 16 1/2 inches
height: 30 1/2 inches
Mounting 46 1/4 - 50 Inches
Height:

Sideloader Tuckaway™ Lifters

This TuckAway® model was developed specifically for side-loaders, with an extra long arc of motion to dump over a variety of sill heights. The D6073 mounts at a height of 46 1/4" - 50" in order to suit your application. Minimal greasing for less maintenance and various powder coat colors to fit your company or truck design.

[More](#)

D6073X-
27k

Load Type: Sideload
Description: US 2-Bar; Type B (ANSI Z245.60-2008)
Operation: Helical Rotary Actuator with 27,000 inch-lbs of torque at 3000 psi
width: 16 3/4 inches
height: 40-31 3/4 inches
Mounting 40 - 53 inches
Height:

Sideloader Tuckaway™ Lifters

The TuckAway® model was developed specifically for side-loaders, with an extra long arc of motion to dump over a variety of sill heights. The D6073x has a mounting height of 40"-53" inches to suit your application. If your application requires more customization, Perkins' fully staffed engineering department is available for quick and practical custom applications.

[More](#)

D6080-
27k

Load Type: Rearload without kick-bar
Description: US 2-Bar; Type B (ANSI Z245.60-2008)
Operation: Helical Rotary Actuator with 27,000 inch-lbs of torque at 3000 psi
width: 16 3/4 inches
height: 23 3/4 inches
Mounting 38 1/2 - 41 inches
Height:

Rotary TuckAway™ Lifter

The original TuckAway® is a proven field veteran known across the waste industry for dependability and performance. The TuckAway® design stores the lifter under the hopper when the lifter is not in use.

[More](#)

D6098-
47-27k

Load Type: Sideload
Description: Automated; Type G (ANSI Z245.60-2008)
Operation: Helical Rotary Actuator with 27,000 inch-lbs of torque at 3000 psi
width: 34 7/8 inches
height: 30 3/4 inches
Mounting 47 1/2 inches

Auto-Arm Lifter

This barrel-grabber style cart lifter features hydraulically folding arms that get out of the way for hand loading items. Many different arm lengths are available to suit any size application from rear-loaders to side-loaders of any height. When in use, the arms are capable of fitting a large assortment of styles and sizes of plastic carts.

[More](#)

Height:

[1](#) [2](#) [3](#) [4](#) [5](#) [Next](#)

* **Please Note:** It is the purchaser's responsibility to determine product suitability for a given application. Perkins Manufacturing cannot be held liable for errors or omissions. Please call Perkins Manufacturing **(708) 482-9500** for assistance in choosing a cart lifter.



© Copyright 2018 Perkins Manufacturing Company - All rights reserved© Copyright 2018 Perkins Manufacturing Company - All rights reserved
[Terms of Use](#) | [Privacy](#) | [Sitemap](#) | [Contact Perkins](#)